

KOMASU

Mini Tiller

(ES500C-2)
881403009



(ES500C-3)
881403010



Optional :-
Ridger
(881403006)



Model	ES500C-2	ES500C-3
Machine Dimension(L x W x H)mm	1380 x 650 x 970	
Max. Tilling Scope(mm)	1000	500 ~ 1000
Tilling Depth(mm)	150 ~ 300	150 ~ 250
Gear Shifting	-1, 0 ; 2, 1, 0	DRIVE NEUTRAL REVERSE SWIFT NEUTRAL TARDY
Transmission Type	Belt	
Transmission Oil Capacity(L)	0.95	~
Engine Model	168FB	168FB/A(GX160)
Engine Type	OHV25°, Single Cylinder, 4 Stroke, Forced Air Cooling	
Bore x Stroke	φ 68 x 54	
Displacement(ml)	196	
Max Power HP / rpm	6.5 / 3600	
Max. Torque N.m/rpm	10.5 / 2500	12.0 / 2500
Fuel Tank Capacity(L)	3.6	
Engine Oil Capacity(L)	0.6	
Min. Fuel Consumption g/kw.h	313	395
Standard Features	Front Wheel, Fender	
N.W / G.W (kg)	63 / 73	
Dimension (L x W x H)mm	820 x 375 x 780	830 x 375 x 770

***Product's specification may subject to change without further notice.
***Actual product may slightly differ from pictures shown.

ESM341
(30/03/11)