



Mist

Cooler

Features :-

1. Design with 3 fan fixed directions overcomes the defect of only one fixed positional ceiling rotary fans.
2. Centrifugal atomization design, without nozzle, no need for water filtrations equipment.
3. Adjustable misting volume, low noise.
4. Atomization and air-delivery driven by separate motor, convenient to use and easy to maintain.
5. The fan surface with powder coating, good rust prevention and long service life.
6. Motor with low temperature rise design, steady performance, long life and good overload protection.
7. Protective device for pump running when water is over.
8. 90 degrees oscillation, 3 speeds.



MFS-18



MFW-26



MFS-26

Applications :-

**Air cooling, Humidity control,
Disinfection, Dust & Odor control.**

Open-air restaurants.

Work sites.

Factory and warehouses.

Green houses, livestock farms.

Sport ground and swimming pools.

For all outdoor area cooling.

Model	Blade diameter	Motor	Water Tank Capacity (Approximately)	Effective use area	Max-misting volume	Max delivery distance of mist	Temperature Drop	Air Volume	Noise	Height
	mm	W	Litre	m ²	L/h	m	°C	m ³ /min	db	mm
MFS-18	450(18")	125	-	-	1.5	-	-	84	55	1545
MFS-26	650(26")	287	20	35	7.5	15	4-6	220	68	1945
MFW-26	650(26")	325	-	35	7.5	15	4-6	220	68	1140

***Product's specification may subject to change without further notice.

***Actual product may slightly differ from pictures shown.