

**Driven by  
Pneumatic**



#### Application:-

- ❑ It is suitable for tunnel, basement, ship building, electric soldering and waste gas exhaust.
- ❑ Perfect for exhaust /ventilation & spot cooling in hazardous environments.
- ❑ Can easily be stacked during use, transportation and storage.
- ❑ Capability to connect up to 125 feet (38m) of straight duct.
- ❑ Protective guard.
- ❑ Large fan blades generates greater air flow for increased efficiency.
- ❑ Plastic blades are used for utmost safety.
- ❑ High density polypropylene housing for durability.
- ❑ Variable speed control by air input.

**Model  
160016**



# Portable Blower (Pneumatic Type)



**Model  
110012**

Model	110012	160016
Size	12"(300mm)	16"(400mm)
Operating Pressure	6kg/cm <sup>2</sup>	
Max. Operating Pressure	7kg/cm <sup>2</sup>	
Max Rated	3000 m <sup>3</sup> /h	5300 m <sup>3</sup> /h
Wheel Speed	3450rpm	
Gross Weight	15kg	20kg
Net Weight	14kg	19kg
Carton Size	(510 x 500 x 550)mm	(460 x 560 x 690)mm



Stock code:  
110012 880217037  
160016 880217038



**Driven by  
Pneumatic**

\*\*\*Product's specification may subject to change without further notice.  
\*\*\*Actual product may slightly differ from pictures shown.

ESM374  
(30/07/14)